

Lagerprodukter

Produktkod	Material	Bredd LWM	Längd SWM	Delning LWM	Matning	Godstjocklek	Öppen maska	Öppen area (90° grader)	Vikt
		mm	mm	mm	mm	mm	mm	%	kg/m ²
2082301M	CR	1000	2000	10	1	1	7 x 4	60	2,7
2082331M	CR	1000	2000	20	2	1,5	14 x 6,5	60	5,2
2082354M	CR	1000	2000	30	2	2	22,5 x 9	71	4,2
2082355M	CR	1250	2440	30	2	2	22,5 x 9	71	4,2
2082386M	CR	1000	2000	42,2	2,5	1,5	33 x 14,5	72	3,3
2081009M	HR	1000	2000	50	3	3	36 x 17	76	5,9
2081010M	HR	1250	2440	50	3	3	36 x 17	76	5,9
2081026M	HR	1250	2440	60	3	3	49 x 21	78	5,1
2081042M	HR	1250	2440	60	6	5	42,5 x 17	56	16,7
2081087M	HR	1250	2440	85	3	3	72 x 32	82	3,9
2081109M	HR	1250	2440	85	7	5	68 x 29	61	12,9
2081127M	HR	1250	2440	115	3,5	3	101 x 45	84	3,8

Material

CR: obehandlat kallvalsat stål. DC01 eller motsvarande.

HR: obehandlat varmvalsat stål. S235 eller motsvarande.

Allmänna toleranser

(noggrannare toleranser kan avtalas ordervis)

Bredd LWM -5/+30 mm

Längd SWM -0/+1 maska eller -0/+30 mm (den som är större)

Korsmått ± 5 mm

